

LEPA4MLIIS 5000 mAh (4700 mAh minimum) 36.0 Wh | IP68 Rated



ESM-50-HA4-04

IP67 Rated, Emergency Button
Dual PTT, Auto-Nexus Connector
2-year Warranty



EC2M-HA3-D Dual Unit Charger Desktop / In-Vehicle 2-year Warranty

L3Harris XL-200P Series

XL-185Pi | XL-200Pi

Intrinsically Safe, High-Capacity Battery

SPECIFICATIONS – LEPA4MLIIS

DIMENSIONS (H X W X D)	77.3 x 57.9 x 32.3 mm / 3.04 x 2.28 x 1.27 in
WEIGHT	196 g / 6.9 oz.
CHEMISTRY	Li-lon
VOLTAGE	7.2V
CELL TYPE	Samsung INR21700-50E
OPERATING TEMPERATURE	-20° C to +60° C (discharge)
CERTIFICATION	TIA-4950 / UL 913 5 [™] Edition

INTRINSICALLY SAFE Replaces XL-PA4M / 14035-5050-02



EVC-HA3
Rugged In-Vehicle Charger
4-Unit Model Also Available
2-year Warranty



EC12M-HA3-D Twelve-Unit Charger Desktop / In-Vehicle 2-year Warranty

LEPA4MLIIS FEATURES

- IP68 rated to withstand dust, dirt and sand, and is waterproof to a depth of 1 meter for up to 30 minutes.
- Similar in size to L3Harris battery XL-PA4M.
- Rugged design ensures greater reliability in the field.

Shop additional accessories for L3Harris XL-200P radios at www.powerproducts.com.

